CLAIMS

We claim:

10   1. A three dimensional model re-parameterization computer system comprising:

a re-parameterization process that re-parameterizes one or more Catmull-Clark models to

create a re-parameterized model, each of the Catmull-Clark models having one or more

extraordinary vertices and one or more adjacent iso-parameter lines that have a natural

15   spacing that changes, the re-parameterized model having iso-parameter lines with a new

spacing that is different than the natural spacing as the lines approach the extraordinary

vertex.

20   2. A three dimensional model re-parameterization computer system comprising:

one or more Catmull-Clark models, each of the models having one or more surfaces and

one or more extraordinary vertices, where one or more adjacent iso-parameter lines have

a natural spacing between them that changes as the iso-parameter lines approach the

25   extraordinary vertex; and

a re-parameterization process that re-parameterizes the model so that one or more of the extraordinary vertices have adjacent iso-parameter lines with a new spacing that is different than the natural spacing as the lines approach the extraordinary vertex.

3. A system, as in claim 1, where the derivatives evaluated at one or more parameter values of one or more limit surfaces of subdivision of the Catmull-Clark model approach zero as one or more parameter positions approach the extraordinary vertex.

4. A system, as in claim 1, where the derivatives evaluated at one or more parameter values of a limit surface of subdivision of the Catmull-Clark model approach an actual derivative of the limit surface at the extraordinary point as one or more parameter positions approach the extraordinary vertex.

5. A system, as in claim 1, where the new spacing decreases as the iso-parameter lines approach one or more of the extraordinary vertices.

6. A method, as in claim 1, where the new spacing is uniform as the iso-parameter lines approach one or more of the extraordinary vertices.

7. A method for surface re-parameterization of a surface around extraordinary vertices of a computer three-dimensional Catmull-Clark model with a plurality of vertices, at least one extraordinary vertex, and iso-parameter lines with a natural spacing, the method comprising the step of:

5

re-parameterizating one or more of the subdivision surfaces of the Catmull-Clark model

around one or more of the extraordinary vertices into a re-parameterized surface with a

new spacing that is different than the natural spacing as the iso-parameter lines approach

the extraordinary vertex.

10

8. A method, as in claim 7, further comprising the step of evaluating the re-parameterized

surface at one or more parameter positions.

9. A method, as in claim 7, where the re-parameterizing comprises the following steps:

15

computing four subdominant eigenvalues corresponding to each of the vertices of a face,

being face vertices, of a quadrilateral mesh containing one or more points being

evaluated;

20 re-parameterizing the surface around each of the face vertices using a re-parameterization

of vanishing derivatives, such that

$$\mathbf{x} \xrightarrow{\;F_k\;} |\,\mathbf{x}\,|^{\alpha_k - 1}\, \mathbf{x}$$, where k identifies the face vertex and $\mathbf{x}$ is the point being

evaluated in a parameter domain, and the re-parameterization is subject to the constraint

25

$$\alpha_k > -\frac{\log 2}{\log \lambda_k}$$

5   where λ_k is the subdominant eigenvalue corresponding to face vertex k and α_k is an

exponent parameter of the re-parameterization for the respective face vertex; and

blending the re-parameterizations of each face vertex that is re-parameterized.

10

10. A method, as in claim 7, where the re-parameterizing comprises the following steps:

computing a characteristic map corresponding to each of the vertices of a face, being face

vertices, of a quadrilateral mesh containing one or more points being evaluated;

15

computing an inverse characteristic map for each of the face vertices; and

blending the inverse characteristic maps of the four face vertices to create the re-

parameterization.

20

11. A method, as in claim 10, where the characteristic map is used to obtain a

continuously differentiable parameterization around one or more of the extraordinary

vertices.

25

12. A method, as in claim 10, where the inverse characteristic map is computed by

locating a layer on the surface and a polynomial patch within that layer that contains the

5   point to be evaluated and then computing a re-parametrized position of the input point by

polynomial patch inversion.

13. A method, as in claim 7, where the blending is a blending of the re-parameterizations

of two or more extraordinary vertices.

10

14. A method, as in claim 7, where the new spacing decreases as the iso-parameter lines

approach one or more of the extraordinary vertices.

15. A method, as in claim 7, where the new spacing is uniform as the iso-parameter lines

15   approach one or more of the extraordinary vertices.

16. A system for surface re-parameterization of a surface around extraordinary vertices of

a computer three-dimensional Catmull-Clark model comprising:

20   means for re-parameterizating of one or more subdivision surfaces of the Catmull-Clark

model with a plurality of vertices and at least one extraordinary and that has iso-

parameter lines with spacing that is different than an original natural spacing, as the iso-

parameter lines approach the vertex.

25   17. A computer program product for surface re-parameterization of a surface around

extraordinary vertices of a computer three dimensional Catmull-Clark model, the

5   computer program product having a method stored on one or more computer memory

medium, the method comprising the step of:

re-parameterizating of one or more subdivision surfaces of the Catmull-Clark model with

a plurality of vertices and at least one extraordinary and that has iso-parameter lines with

10   spacing that is different than an original natural spacing, as the iso-parameter lines

approach the vertex.